

1. Identification

| | | | |
|---|--|--------------------------------|--|
| Product identifier | SONAX PROFILINE NP 03-06 | | |
| Other means of identification | | | |
| Synonyms | 02081410, 02083000, 02085000 | | |
| Recommended use | Car Care | | |
| Recommended restrictions | None known. | | |
| Manufacturer/Importer/Supplier/Distributor information | | | |
| Manufacturer | | | |
| Company name | Sonax GmbH | | |
| Address | Münchener Strasse 75 D-86633 Neuburg/Donau Germany | | |
| Telephone | Phone: | 0049 84 31 53-0 | |
| E-mail | info@sonax.com | | |
| Emergency phone number | Emergency CONTACT (24 hr) | GBK/Infotrac ID 91785: | |
| | . | (USA domestic) 1 800 535 5053 | |
| | . | or international (001) 352 323 | |
| Supplier | Vision Investments, LLC 17414 Tiller Court Westfield, IN 46074 US Email: info@sonaxusa.com Phone: 1-317-295-7056 | | |

2. Hazard identification

| | | | |
|--|--|--|--|
| Physical hazards | Not classified. | | |
| Health hazards | Not classified. | | |
| Environmental hazards | Not classified. | | |
| WHMIS 2015 defined hazards | Not classified | | |
| Label elements | | | |
| Hazard symbol | None. | | |
| Signal word | None. | | |
| Hazard statement | The mixture does not meet the criteria for classification. | | |
| Precautionary statement | | | |
| Prevention | Observe good industrial hygiene practices. | | |
| Response | Wash hands after handling. | | |
| Storage | Store away from incompatible materials. | | |
| Disposal | Dispose of waste and residues in accordance with local authority requirements. | | |
| WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC) | None known | | |
| WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC) | None known | | |
| Hazard(s) not otherwise classified (HNOC) | None known. | | |
| Supplemental information | None. | | |

3. Composition/Information on ingredients

Mixture

| Chemical name | Common name and synonyms | CAS number | % |
|--|--------------------------|------------|--------|
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based | | 72623-86-0 | 5 - 10 |
| Distillates (petroleum), hydrotreated middle | | 64742-46-7 | 3 - 7 |
| 1,2-Propanediol | | 57-55-6 | 1 - 5 |
| Propylene glycol monomethyl ether | | 107-98-2 | 1 - 5 |
| Aluminium oxide | | 1344-28-1 | 1 - 5 |
| Distillates (petroleum), light hydrotreated | | 64742-47-8 | 1 - 5 |
| Glycerol | | 56-81-5 | 1 - 5 |

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

| | |
|---|--|
| Inhalation | If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention. |
| Skin contact | Flush with cool water. Wash with soap and water. Obtain medical attention if irritation persists. |
| Eye contact | Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical attention if irritation persists. |
| Ingestion | Rinse mouth. If ingestion of a large amount does occur, call a poison control centre immediately. |
| Most important symptoms/effects, acute and delayed | Direct contact with eyes may cause temporary irritation. |
| Indication of immediate medical attention and special treatment needed | Treat symptomatically. |
| General information | Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. |

5. Fire-fighting measures

| | |
|--|---|
| Suitable extinguishing media | Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide. |
| Unsuitable extinguishing media | Not available. |
| Specific hazards arising from the chemical | Not available. |
| Special protective equipment and precautions for firefighters | Self-contained breathing apparatus and full protective clothing must be worn in case of fire. |
| Fire-fighting equipment/instructions | Move containers from fire area if you can do so without risk. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. |
| General fire hazards | No unusual fire or explosion hazards noted. |
| Hazardous combustion products | May include and are not limited to: Oxides of carbon. |

6. Accidental release measures

| | |
|--|--|
| Personal precautions, protective equipment and emergency procedures | Keep out of low areas. Keep people away from and upwind of spill/leak. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. For personal protection, see section 8 of the SDS. |
| Methods and materials for containment and cleaning up | Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Use water spray to reduce vapours or divert vapour cloud drift. Following product recovery, flush area with water. Clean surface thoroughly to remove residual contamination. Prevent entry into waterways, sewer, basements or confined areas. For waste disposal, see section 13 of the SDS. |
| Environmental precautions | Avoid discharge into drains, water courses or onto the ground. |

7. Handling and storage

| | |
|---|---|
| Precautions for safe handling | Avoid contact with eyes, skin and clothing. Use care in handling/storage. |
| Conditions for safe storage, including any incompatibilities | Store in original tightly closed container. Store in a cool, dry, well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep out of reach of children. |

8. Exposure controls/Personal protection

Occupational exposure limits

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

| Components | Type | Value | Form |
|---|------|----------------------|---------|
| Aluminium oxide (CAS 1344-28-1) | TWA | 10 mg/m3 | |
| Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) | STEL | 10 mg/m3 | Mist. |
| | TWA | 5 mg/m3 | Mist. |
| Distillates (petroleum), light hydrotreated (CAS 64742-47-8) | TWA | 200 mg/m3 | Vapour. |
| Glycerol (CAS 56-81-5) | TWA | 10 mg/m3 | Mist. |
| Propylene glycol monomethyl ether (CAS 107-98-2) | STEL | 553 mg/m3 | |
| | | 150 ppm | |
| | TWA | 369 mg/m3 100 ppm | |

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

| Components | Type | Value | Form |
|---|------|-----------|------------------|
| Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) | TWA | 1 mg/m3 | Mist. |
| Distillates (petroleum), light hydrotreated (CAS 64742-47-8) | TWA | 200 mg/m3 | Non-aerosol. |
| Glycerol (CAS 56-81-5) | TWA | 3 mg/m3 | Respirable mist. |
| | | 10 mg/m3 | Mist. |
| Propylene glycol monomethyl ether (CAS 107-98-2) | STEL | 100 ppm | |
| | TWA | 50 ppm | |

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

| Components | Type | Value | Form |
|---|------|---------|---------------------|
| Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) | TWA | 5 mg/m3 | Inhalable fraction. |
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0) | TWA | 5 mg/m3 | Inhalable fraction. |
| Propylene glycol monomethyl ether (CAS 107-98-2) | STEL | 100 ppm | |
| | TWA | 50 ppm | |

Canada. New Brunswick OELs: Threshold Limit Values (TLVs) Based on the 1991 and 1997 ACGIH TLVs and BEIs Publication (New Brunswick Regulation 91-191), as amended

| Components | Type | Value | Form |
|---|------|-----------|-------|
| Aluminium oxide (CAS 1344-28-1) | TWA | 10 mg/m3 | |
| Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) | STEL | 10 mg/m3 | Mist. |
| | TWA | 5 mg/m3 | Mist. |
| Glycerol (CAS 56-81-5) | TWA | 10 mg/m3 | Mist. |
| Propylene glycol monomethyl ether (CAS 107-98-2) | STEL | 553 mg/m3 | |

Canada. New Brunswick OELs: Threshold Limit Values (TLVs) Based on the 1991 and 1997 ACGIH TLVs and BEIs Publication (New Brunswick Regulation 91-191), as amended

| Components | Type | Value | Form |
|------------|------|-----------|------|
| | | 150 ppm | |
| | TWA | 369 mg/m3 | |
| | | 100 ppm | |

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

| Components | Type | Value | Form |
|---|------|-----------|---------------------|
| 1,2-Propanediol (CAS 57-55-6) | TWA | 155 mg/m3 | Vapour and aerosol. |
| | | 10 mg/m3 | Aerosol |
| | | 50 ppm | Vapour and aerosol. |
| Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) | TWA | 5 mg/m3 | Inhalable fraction. |
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0) | TWA | 5 mg/m3 | Inhalable fraction. |
| Propylene glycol monomethyl ether (CAS 107-98-2) | STEL | 100 ppm | |
| | TWA | 50 ppm | |

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

| Components | Type | Value | Form |
|---|------|-----------|-------------|
| Aluminium oxide (CAS 1344-28-1) | TWA | 10 mg/m3 | Total dust. |
| Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) | STEL | 10 mg/m3 | Mist. |
| | TWA | 5 mg/m3 | Mist. |
| Glycerol (CAS 56-81-5) | TWA | 10 mg/m3 | Mist. |
| Propylene glycol monomethyl ether (CAS 107-98-2) | STEL | 553 mg/m3 | |
| | | 150 ppm | |
| | TWA | 369 mg/m3 | |
| | | 100 ppm | |

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)

| Components | Type | Value | Form |
|---|-----------|-----------|---------|
| Aluminium oxide (CAS 1344-28-1) | 15 minute | 20 mg/m3 | |
| | 8 hour | 10 mg/m3 | |
| Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) | 15 minute | 10 mg/m3 | |
| | 8 hour | 5 mg/m3 | |
| Distillates (petroleum), light hydrotreated (CAS 64742-47-8) | 15 minute | 250 mg/m3 | Vapour. |
| | 8 hour | 200 mg/m3 | Vapour. |
| Glycerol (CAS 56-81-5) | 15 minute | 20 mg/m3 | Mist. |
| | 8 hour | 10 mg/m3 | Mist. |
| Propylene glycol monomethyl ether (CAS 107-98-2) | 15 minute | 150 ppm | |
| | 8 hour | 100 ppm | |

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value | Form |
|---|------|----------|----------------------|
| Aluminium oxide (CAS 1344-28-1) | PEL | 5 mg/m3 | Respirable fraction. |
| | | 15 mg/m3 | Total dust. |
| Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) | PEL | 5 mg/m3 | Mist. |
| | | | |
| Glycerol (CAS 56-81-5) | PEL | 5 mg/m3 | Respirable fraction. |
| | | 15 mg/m3 | Total dust. |

US. OSHA Table Z-3 (29 CFR 1910.1000)

| Components | Type | Value | Form |
|---------------------------------|------|----------|----------------------|
| Aluminium oxide (CAS 1344-28-1) | TWA | 5 mg/m3 | Respirable fraction. |
| | | 15 mg/m3 | Total dust. |
| | | 50 Mppcf | Total dust. |
| | | 15 Mppcf | Respirable fraction. |
| Glycerol (CAS 56-81-5) | TWA | 5 mg/m3 | Respirable fraction. |
| | | 15 mg/m3 | Total dust. |
| | | 50 Mppcf | Total dust. |
| | | 15 Mppcf | Respirable fraction. |

US. ACGIH Threshold Limit Values

| Components | Type | Value | Form |
|---|------|---------|---------------------|
| Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) | TWA | 5 mg/m3 | Inhalable fraction. |
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0) | TWA | 5 mg/m3 | Inhalable fraction. |
| Propylene glycol monomethyl ether (CAS 107-98-2) | STEL | 100 ppm | |
| | TWA | 50 ppm | |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value | Form |
|---|------|----------------------|-------|
| Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) | STEL | 10 mg/m3 | Mist. |
| | TWA | 5 mg/m3 | Mist. |
| Distillates (petroleum), light hydrotreated (CAS 64742-47-8) | TWA | 100 mg/m3 | |
| Propylene glycol monomethyl ether (CAS 107-98-2) | STEL | 540 mg/m3 | |
| | | 150 ppm | |
| | TWA | 360 mg/m3 100 ppm | |

US. Workplace Environmental Exposure Level (WEEL) Guides

| Components | Type | Value | Form |
|-------------------------------|------|----------|---------|
| 1,2-Propanediol (CAS 57-55-6) | TWA | 10 mg/m3 | Aerosol |

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines**Canada - Alberta OELs: Skin designation**

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

Can be absorbed through the skin.

Canada - British Columbia OELs: Skin designation

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

Can be absorbed through the skin.

Canada - Saskatchewan OELs: Skin designation

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

Can be absorbed through the skin.

| | |
|--|---|
| Appropriate engineering controls | Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. |
| Individual protection measures, such as personal protective equipment | |
| Eye/face protection | Not required under normal use conditions. |
| Skin protection | |
| Hand protection | Not required under normal use conditions. |
| Other | As required by employer code. |
| Respiratory protection | Not normally required if good ventilation is maintained and exposure guidelines are not exceeded. |
| Thermal hazards | Not available. |
| General hygiene considerations | Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. |

9. Physical and chemical properties

| | |
|---|---------------------------|
| Appearance | |
| Physical state | Liquid. |
| Form | Liquid. |
| Colour | White |
| Odour | Solvent-like |
| Odour threshold | Not available. |
| pH | Not available. |
| Melting point/freezing point | Not available. |
| Initial boiling point and boiling range | Not available. |
| Specific gravity | Not available. |
| Flash point | Not available. |
| Evaporation rate | Not available. |
| Flammability (solid, gas) | Not flammable |
| Upper/lower flammability or explosive limits | |
| Flammability limit - lower (%) | Not available. |
| Flammability limit - upper (%) | Not available. |
| Explosive limit - lower (%) | Not available. |
| Explosive limit - upper (%) | Not available. |
| Vapour pressure | Not available. |
| Vapour density | Not available. |
| Relative density | Not available. |
| Solubility(ies) | partly miscible |
| Partition coefficient (n-octanol/water) | Not available. |
| Auto-ignition temperature | Not available. |
| Decomposition temperature | Not available. |
| Viscosity | Not available. |
| Other information | |
| Pour point | Not available. |
| Explosive properties | Not explosive. |
| Kinematic viscosity | > 20.5 mm ² /s |
| Kinematic viscosity temperature | 40 °C (104 °F) |
| Oxidising properties | Not oxidising. |

10. Stability and reactivity

| | |
|---|---|
| Reactivity | This product may react with strong oxidising agents. |
| Possibility of hazardous reactions | Hazardous polymerisation does not occur. |
| Chemical stability | Material is stable under normal conditions. |
| Conditions to avoid | Do not mix with other chemicals. |
| Incompatible materials | Strong oxidising agents. |
| Hazardous decomposition products | May include and are not limited to: Oxides of carbon. |

11. Toxicological information

| | |
|---|--|
| Routes of exposure | Inhalation. Ingestion. Skin contact. Eye contact. |
| Information on likely routes of exposure | |
| Ingestion | May cause stomach distress, nausea or vomiting. |
| Inhalation | Prolonged inhalation may be harmful. |
| Skin contact | No adverse effects due to skin contact are expected. |
| Eye contact | Direct contact with eyes may cause temporary irritation. |
| Symptoms related to the physical, chemical and toxicological characteristics | There are no hazards associated with this product in normal use. |

Information on toxicological effects

Acute toxicity Not known.

| Components | Species | Test Results |
|---|----------------|---|
| 1,2-Propanediol (CAS 57-55-6) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Rabbit | > 2000 mg/kg, 24 Hours, ECHA |
| <i>Inhalation</i> | | |
| LC50 | Rabbit | > 317042 mg/m ³ , 2 Hours, ECHA |
| <i>Oral</i> | | |
| LD50 | Rat | 22000 mg/kg, ECHA |
| Aluminium oxide (CAS 1344-28-1) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Not available | |
| <i>Inhalation</i> | | |
| LC50 | Rat | > 2.3 mg/L, 4 Hours, ECHA 7.6 mg/L, 1 Hours |
| <i>Oral</i> | | |
| LD50 | Rat | > 2000 mg/kg, ECHA |
| Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Rabbit | > 2000 mg/kg, 24 Hours, ECHA |
| <i>Inhalation</i> | | |
| LC50 | Rat | 7640 mg/m ³ , 4 Hours, ECHA 4.6 mg/L, 4 Hours, ECHA |
| <i>Oral</i> | | |
| LD50 | Rat | > 5000 mg/kg, ECHA |
| Distillates (petroleum), light hydrotreated (CAS 64742-47-8) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Rabbit | > 2000 mg/kg, 24 Hours, ECHA |

| Components | Species | Test Results |
|---|--|--|
| <i>Inhalation</i> LC50 | Rat | > 5.3 mg/L, 4 Hours, ECHA |
| <i>Oral</i> LD50 | Rat | > 5000 mg/kg, ECHA |
| Glycerol (CAS 56-81-5) | | |
| Acute | | |
| <i>Dermal</i> LD50 | Guinea pig | 56750 mg/kg, ECHA |
| <i>Inhalation</i> LC50 | Rat | 275000 mg/m ³ , 4 hours, ECHA |
| <i>Oral</i> LD50 | Rat | 11500 mg/kg, ECHA |
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0) | | |
| Acute | | |
| <i>Dermal</i> LD50 | Rabbit | > 2000 mg/kg, 24 Hours, ECHA |
| <i>Inhalation</i> LC50 | Rat | > 5.2 mg/L, 4 Hours, ECHA |
| <i>Oral</i> LD50 | Rat | 5000 mg/kg, ECHA |
| Propylene glycol monomethyl ether (CAS 107-98-2) | | |
| Acute | | |
| <i>Dermal</i> LD50 | Rat | > 2000 mg/kg, ECHA |
| <i>Inhalation</i> LC50 | Rat | 30 mg/l/4h, ECHA |
| <i>Oral</i> LD50 | Rat | 4016 mg/kg, ECHA |
| Skin corrosion/irritation | Prolonged skin contact may cause temporary irritation. | |
| Exposure minutes | Not available. | |
| Erythema value | Not available. | |
| Oedema value | Not available. | |
| Serious eye damage/eye irritation | Direct contact with eyes may cause temporary irritation. | |
| Corneal opacity value | Not available. | |
| Iris lesion value | Not available. | |
| Conjunctival reddening value | Not available. | |
| Conjunctival oedema value | Not available. | |
| Recover days | Not available. | |
| Respiratory or skin sensitisation | | |
| Canada - Alberta OELs: Irritant | | |
| Glycerol (CAS 56-81-5) | | Irritant |
| Respiratory sensitisation | Not a respiratory sensitizer. | |
| Skin sensitisation | This product is not expected to cause skin sensitisation. | |
| Mutagenicity | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. | |
| Carcinogenicity | Not classifiable as to carcinogenicity to humans. | |
| ACGIH Carcinogens | | |
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0) | A2 | Suspected human carcinogen. |
| Canada - Manitoba OELs: carcinogenicity | | |
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0) | | Suspected human carcinogen. |

IARC Monographs. Overall Evaluation of Carcinogenicity

Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)

Volume 33, Supplement 7 - 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not listed.

US NTP Report on Carcinogens: Known carcinogen

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0) Known To Be Human Carcinogen.

| | |
|---|--|
| Reproductive toxicity | This product is not expected to cause reproductive or developmental effects. |
| Teratogenicity | Not available. |
| Specific target organ toxicity - single exposure | Not classified. |
| Specific target organ toxicity - repeated exposure | Not classified. |
| Aspiration hazard | Not an aspiration hazard. |
| Chronic effects | Prolonged inhalation may be harmful. |

12. Ecological information

Ecotoxicity See below

Ecotoxicological data

| Components | | Species | Test Results |
|---|---|---|------------------------------|
| 1,2-Propanediol (CAS 57-55-6) | | | |
| Crustacea | EC50 | Daphnia | 10000 mg/L, 48 Hours |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | > 10000 mg/L, 48 hours |
| Fish | LC50 | Fathead minnow (Pimephales promelas) | 710 mg/L, 96 hours |
| Distillates (petroleum), light hydrotreated (CAS 64742-47-8) | | | |
| Aquatic | | | |
| Fish | LC50 | Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 2.9 mg/L, 96 hours |
| Glycerol (CAS 56-81-5) | | | |
| Aquatic | | | |
| Fish | LC50 | Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 51000 - 57000 mg/L, 96 hours |
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0) | | | |
| Crustacea | EC50 | Daphnia | 1000 mg/L, 48 Hours |
| Propylene glycol monomethyl ether (CAS 107-98-2) | | | |
| Crustacea | EC50 | Daphnia | 23300 mg/L, 48 Hours |
| Persistence and degradability | No data is available on the degradability of any ingredients in the mixture. | | |
| Bioaccumulative potential | | | |
| Mobility in soil | No data available. | | |
| Mobility in general | Not available. | | |
| Other adverse effects | No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component. | | |

13. Disposal considerations

| | |
|--|--|
| Disposal instructions | Collect and reclaim or dispose in sealed containers at licensed waste disposal site. |
| Local disposal regulations | Dispose in accordance with all applicable regulations. |
| Hazardous waste code | The waste code should be assigned in discussion between the user, the producer and the waste disposal company. |
| Waste from residues / unused products | Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). |
| Contaminated packaging | Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. |

14. Transport information

Transport of Dangerous Goods (TDG) Proof of Classification Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.

U.S. Department of Transportation (DOT)

Not regulated as dangerous goods.

Transportation of Dangerous Goods (TDG - Canada)

Not regulated as dangerous goods.

15. Regulatory information

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Distillates (petroleum), light hydrotreated (CAS 64742-47-8) 1 TONNES

Canada Priority Substances List (Second List): Listed substance

Aluminium oxide (CAS 1344-28-1) Listed.

Glycerol (CAS 56-81-5) Listed.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

WHMIS 2015 Exemptions Not applicable

US Federal regulations This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Listed.

Propylene glycol monomethyl ether (CAS 107-98-2) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance No

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

| Chemical name | CAS number | % by wt. |
|-----------------|------------|----------|
| Aluminium oxide | 1344-28-1 | 1 - 5 |

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

US state regulations

US - California Hazardous Substances (Director's): Listed substance

Aluminium oxide (CAS 1344-28-1) Listed.

Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) Listed.

Propylene glycol monomethyl ether (CAS 107-98-2) Listed.

US - Illinois Chemical Safety Act: Listed substance

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

Propylene glycol monomethyl ether (CAS 107-98-2)

US - Louisiana Spill Reporting: Listed substance

Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Listed.

Propylene glycol monomethyl ether (CAS 107-98-2) Listed.

US - Minnesota Haz Subs: Listed substance

1,2-Propanediol (CAS 57-55-6) Listed.

Aluminium oxide (CAS 1344-28-1) Listed.

Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) Listed.

Glycerol (CAS 56-81-5) Listed.

Propylene glycol monomethyl ether (CAS 107-98-2) Listed.

US - Texas Effects Screening Levels: Listed substance

1,2-Propanediol (CAS 57-55-6) Listed.

Aluminium oxide (CAS 1344-28-1) Listed.

Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) Listed.

Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Listed.

Glycerol (CAS 56-81-5) Listed.

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0) Listed.

Propylene glycol monomethyl ether (CAS 107-98-2) Listed.

US. Massachusetts RTK - Substance List

Aluminium oxide (CAS 1344-28-1)

Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

Glycerol (CAS 56-81-5)

Propylene glycol monomethyl ether (CAS 107-98-2)

US. New Jersey Worker and Community Right-to-Know Act

1,2-Propanediol (CAS 57-55-6)

Aluminium oxide (CAS 1344-28-1)

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

Glycerol (CAS 56-81-5)

Propylene glycol monomethyl ether (CAS 107-98-2)

US. Pennsylvania Worker and Community Right-to-Know Law

1,2-Propanediol (CAS 57-55-6)

Aluminium oxide (CAS 1344-28-1)

Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

Glycerol (CAS 56-81-5)

Propylene glycol monomethyl ether (CAS 107-98-2)

US. Rhode Island RTK

1,2-Propanediol (CAS 57-55-6)

Aluminium oxide (CAS 1344-28-1)

Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

Glycerol (CAS 56-81-5)

Propylene glycol monomethyl ether (CAS 107-98-2)

US. California Proposition 65

This product is not subject to warning labeling under the California Proposition 65 regulation.

Inventory status

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|---|------------------------|
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information

| LEGEND | |
|----------|---|
| Severe | 4 |
| Serious | 3 |
| Moderate | 2 |
| Slight | 1 |
| Minimal | 0 |

| | | |
|----------------------------|---|---|
| HEALTH | * | 2 |
| FLAMMABILITY | | 1 |
| PHYSICAL HAZARD | | 0 |
| PERSONAL PROTECTION | | |



Disclaimer

The information in the safety data sheet was written by Dell Tech Laboratories Ltd. (www.delltech.com) based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

| | |
|----------------------------|-----------------|
| Issue date | 19-October-2022 |
| Version No. | 01 |
| Effective date | 19-October-2022 |
| Further information | Not available. |