

1. Identification

Product identifier	SONAX PROFILINE Cut+Finish		
Other means of identification			
Synonyms	02251410, 02253000		
Recommended use	Car Care		
Recommended restrictions	None known.		
Manufacturer/Importer/Supplier/Distributor information			
Manufacturer			
Company name	Sonax GmbH		
Address	Münchener Strasse 75 D-86633 Neuburg/Donau Germany		
Telephone	Phone:	0049 84 31 53-0	
E-mail	info@sonax.com		
Emergency phone number	Emergency CONTACT (24 hr)	GBK/Infotrac ID 91785:	
	.	(USA domestic) 1 800 535 5053	
	.	or international (001) 352 323	
Supplier	Vision Investments, LLC 17414 Tiller Court Westfield, IN 46074 US Email: info@sonaxusa.com Phone: 1-317-295-7056		

2. Hazard identification

Physical hazards	Not classified.		
Health hazards	Not classified.		
Environmental hazards	Not classified.		
WHMIS 2015 defined hazards	Not classified		
Label elements			
Hazard symbol	None.		
Signal word	None.		
Hazard statement	The mixture does not meet the criteria for classification.		
Precautionary statement			
Prevention	Observe good industrial hygiene practices.		
Response	Wash hands after handling.		
Storage	Store away from incompatible materials.		
Disposal	Dispose of waste and residues in accordance with local authority requirements.		
WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC)	None known		
WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC)	None known		
Hazard(s) not otherwise classified (HNOC)	None known.		
Supplemental information	None.		

3. Composition/Information on ingredients

Mixture

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), hydrotreated middle		64742-46-7	5 - 10
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based		72623-86-0	5 - 10
1,2-Propanediol		57-55-6	3 - 7
Aluminium oxide		1344-28-1	1 - 5
Distillates (petroleum), light hydrotreated		64742-47-8	1 - 5
Glycerol		56-81-5	1 - 5

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret.
US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

4. First-aid measures

Inhalation	If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.
Skin contact	Flush with cool water. Wash with soap and water. Obtain medical attention if irritation persists.
Eye contact	Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical attention if irritation persists.
Ingestion	Do not induce vomiting. Never give anything by mouth if victim is unconscious or is convulsing. Obtain medical attention.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Keep out of reach of children.

5. Fire-fighting measures

Suitable extinguishing media	Water spray. Foam. Dry chemical. Carbon dioxide.
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	Not available.
Special protective equipment and precautions for firefighters	Firefighters should wear full protective clothing including self-contained breathing apparatus.
Fire-fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.
Hazardous combustion products	Not available.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep out of low areas. Keep people away from and upwind of spill/leak. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Stop leak if you can do so without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Clean surface thoroughly to remove residual contamination. Following product recovery, flush area with water. Prevent entry into waterways, sewer, basements or confined areas. For waste disposal, see section 13 of the SDS.
Environmental precautions	Do not discharge into lakes, streams, ponds or public waters.

7. Handling and storage

Precautions for safe handling	Use according to package label instructions. Ensure adequate ventilation. Avoid prolonged exposure. Wash thoroughly after handling. Use good industrial hygiene practices in handling this material.
Conditions for safe storage, including any incompatibilities	Protect from freezing. Keep at temperatures between 20 and 25°C (68-77°F). Store in a cool, dry, well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep out of reach of children.

8. Exposure controls/Personal protection

Occupational exposure limits

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
Aluminium oxide (CAS 1344-28-1)	TWA	10 mg/m3	
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	TWA	200 mg/m3	Vapour.
Glycerol (CAS 56-81-5)	TWA	10 mg/m3	Mist.

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	TWA	1 mg/m3	Mist.
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	TWA	200 mg/m3	Non-aerosol.
Glycerol (CAS 56-81-5)	TWA	3 mg/m3	Respirable mist.
		10 mg/m3	Mist.

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	TWA	5 mg/m3	Inhalable fraction.
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0)	TWA	5 mg/m3	Inhalable fraction.

Canada. New Brunswick OELs: Threshold Limit Values (TLVs) Based on the 1991 and 1997 ACGIH TLVs and BEIs Publication (New Brunswick Regulation 91-191), as amended

Components	Type	Value	Form
Aluminium oxide (CAS 1344-28-1)	TWA	10 mg/m3	
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Glycerol (CAS 56-81-5)	TWA	10 mg/m3	Mist.

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value	Form
1,2-Propanediol (CAS 57-55-6)	TWA	155 mg/m3	Vapour and aerosol.
		10 mg/m3	Aerosol

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value	Form
		50 ppm	Vapour and aerosol.
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	TWA	5 mg/m3	Inhalable fraction.
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0)	TWA	5 mg/m3	Inhalable fraction.

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Type	Value	Form
Aluminium oxide (CAS 1344-28-1)	TWA	10 mg/m3	Total dust.
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Glycerol (CAS 56-81-5)	TWA	10 mg/m3	Mist.

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)

Components	Type	Value	Form
Aluminium oxide (CAS 1344-28-1)	15 minute	20 mg/m3	
	8 hour	10 mg/m3	
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	15 minute	10 mg/m3	
	8 hour	5 mg/m3	
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	15 minute	250 mg/m3	Vapour.
	8 hour	200 mg/m3	Vapour.
Glycerol (CAS 56-81-5)	15 minute	20 mg/m3	Mist.
	8 hour	10 mg/m3	Mist.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Aluminium oxide (CAS 1344-28-1)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	PEL	5 mg/m3	Mist.
Glycerol (CAS 56-81-5)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Aluminium oxide (CAS 1344-28-1)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 Mppcf	Total dust.
		15 Mppcf	Respirable fraction.
Glycerol (CAS 56-81-5)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 Mppcf	Total dust.
		15 Mppcf	Respirable fraction.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	TWA	5 mg/m3	Inhalable fraction.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0)	TWA	5 mg/m ³	Inhalable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	STEL	10 mg/m ³	Mist.
	TWA	5 mg/m ³	Mist.
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	TWA	100 mg/m ³	

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value	Form
1,2-Propanediol (CAS 57-55-6)	TWA	10 mg/m ³	Aerosol

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines**Canada - Alberta OELs: Skin designation**

Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Can be absorbed through the skin.

Canada - British Columbia OELs: Skin designation

Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Can be absorbed through the skin.

Canada - Saskatchewan OELs: Skin designation

Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Not normally required when used as directed.

Skin protection

Hand protection Not normally required when used as directed.

Other Wear appropriate chemical resistant clothing.

Respiratory protection Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

Thermal hazards Not available.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Liquid.
Colour	White
Odour	Solvent-like
Odour threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Specific gravity	Not available.

Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not flammable
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	Not available.
Solubility(ies)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Pour point	Not available.
Density	0.98 - 0.99 g/cm ³
Explosive properties	Not explosive.
Kinematic viscosity	> 20.5 mm ² /s
Kinematic viscosity temperature	40 °C (104 °F)
Oxidising properties	Not oxidising.

10. Stability and reactivity

Reactivity	This product may react with oxidizing agents.
Possibility of hazardous reactions	Hazardous polymerisation does not occur.
Chemical stability	Stable under recommended storage conditions.
Conditions to avoid	Do not mix with other chemicals.
Incompatible materials	Oxidizers.
Hazardous decomposition products	Not available.

11. Toxicological information

Routes of exposure	Inhalation. Ingestion. Skin contact. Eye contact.
Information on likely routes of exposure	
Ingestion	May cause stomach distress, nausea or vomiting.
Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	No adverse effects due to eye contact are expected.
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity See below.

Components	Species	Test Results
1,2-Propanediol (CAS 57-55-6)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours, ECHA

Components	Species	Test Results
<i>Inhalation</i>		
LC50	Rabbit	> 317042 mg/m ³ , 2 Hours, ECHA
<i>Oral</i>		
LD50	Rat	22000 mg/kg, ECHA
Aluminium oxide (CAS 1344-28-1)		
Acute		
<i>Dermal</i>		
LD50	Not available	
<i>Inhalation</i>		
LC50	Rat	> 2.3 mg/L, 4 Hours, ECHA 7.6 mg/L, 1 Hours
<i>Oral</i>		
LD50	Rat	> 2000 mg/kg, ECHA
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	7640 mg/m ³ , 4 Hours, ECHA 4.6 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg, ECHA
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	> 5.3 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg, ECHA
Glycerol (CAS 56-81-5)		
Acute		
<i>Dermal</i>		
LD50	Guinea pig	56750 mg/kg, ECHA
<i>Inhalation</i>		
LC50	Rat	275000 mg/m ³ , 4 hours, ECHA
<i>Oral</i>		
LD50	Rat	11500 mg/kg, ECHA
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	> 5.2 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	5000 mg/kg, ECHA
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Exposure minutes	Not available.	
Erythema value	Not available.	
Oedema value	Not available.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Corneal opacity value	Not available.	

Iris lesion value Not available.
 Conjunctival reddening value Not available.
 Conjunctival oedema value Not available.
 Recover days Not available.

Respiratory or skin sensitisation

Canada - Alberta OELs: Irritant

Glycerol (CAS 56-81-5) Irritant

Respiratory sensitisation Not a respiratory sensitizer.

Skin sensitisation This product is not expected to cause skin sensitisation.

Mutagenicity

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity

Not classifiable as to carcinogenicity to humans.

ACGIH Carcinogens

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0) A2 Suspected human carcinogen.

Canada - Manitoba OELs: carcinogenicity

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0) Suspected human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) Volume 33, Supplement 7 - 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not listed.

US NTP Report on Carcinogens: Known carcinogen

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0) Known To Be Human Carcinogen.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Teratogenicity

Not available.

Specific target organ toxicity - single exposure

Not classified.

Specific target organ toxicity - repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

Chronic effects

Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity

See below

Ecotoxicological data

Components	Species	Test Results
1,2-Propanediol (CAS 57-55-6)		
Crustacea	EC50 Daphnia	10000 mg/L, 48 Hours
Aquatic		
Crustacea	EC50 Water flea (Daphnia magna)	> 10000 mg/L, 48 hours
Fish	LC50 Fathead minnow (Pimephales promelas)	710 mg/L, 96 hours
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)		
Aquatic		
Fish	LC50 Rainbow trout, donaldson trout (Oncorhynchus mykiss)	2.9 mg/L, 96 hours
Glycerol (CAS 56-81-5)		
Aquatic		
Fish	LC50 Rainbow trout, donaldson trout (Oncorhynchus mykiss)	51000 - 57000 mg/L, 96 hours
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0)		
Crustacea	EC50 Daphnia	1000 mg/L, 48 Hours

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Mobility in soil	No data available.
Mobility in general	Not available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Review federal, state and local government requirements prior to disposal.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

Transport of Dangerous Goods (TDG) Proof of Classification	Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.
U.S. Department of Transportation (DOT)	Not regulated as dangerous goods.
Transportation of Dangerous Goods (TDG - Canada)	Not regulated as dangerous goods.

15. Regulatory information

Canadian federal regulations	This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.		
Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number	Distillates (petroleum), light hydrotreated (CAS 64742-47-8) 1 TONNES		
Canada Priority Substances List (Second List): Listed substance	Aluminium oxide (CAS 1344-28-1) Listed. Glycerol (CAS 56-81-5) Listed.		
Export Control List (CEPA 1999, Schedule 3)	Not listed.		
Greenhouse Gases	Not listed.		
Precursor Control Regulations	Not regulated.		
WHMIS 2015 Exemptions	Not applicable		
US Federal regulations	This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.		
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)	Not regulated.		
CERCLA Hazardous Substance List (40 CFR 302.4)	Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Listed.		
SARA 304 Emergency release notification	Not regulated.		
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)	Not listed.		
Superfund Amendments and Reauthorization Act of 1986 (SARA)			
SARA 302 Extremely hazardous substance	No		
SARA 311/312 Hazardous chemical	No		
SARA 313 (TRI reporting)			
Chemical name	CAS number	% by wt.	
Aluminium oxide	1344-28-1	1 - 5	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

US state regulations

US - California Hazardous Substances (Director's): Listed substance

Aluminium oxide (CAS 1344-28-1) Listed.
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) Listed.

US - Illinois Chemical Safety Act: Listed substance

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

US - Louisiana Spill Reporting: Listed substance

Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Listed.

US - Minnesota Haz Subs: Listed substance

1,2-Propanediol (CAS 57-55-6) Listed.
Aluminium oxide (CAS 1344-28-1) Listed.
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) Listed.
Glycerol (CAS 56-81-5) Listed.

US - Texas Effects Screening Levels: Listed substance

1,2-Propanediol (CAS 57-55-6) Listed.
Aluminium oxide (CAS 1344-28-1) Listed.
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) Listed.
Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Listed.
Glycerol (CAS 56-81-5) Listed.
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0) Listed.

US. Massachusetts RTK - Substance List

Aluminium oxide (CAS 1344-28-1)
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)
Glycerol (CAS 56-81-5)

US. New Jersey Worker and Community Right-to-Know Act

1,2-Propanediol (CAS 57-55-6)
Aluminium oxide (CAS 1344-28-1)
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)
Glycerol (CAS 56-81-5)

US. Pennsylvania Worker and Community Right-to-Know Law

1,2-Propanediol (CAS 57-55-6)
Aluminium oxide (CAS 1344-28-1)
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)
Glycerol (CAS 56-81-5)

US. Rhode Island RTK

1,2-Propanediol (CAS 57-55-6)
Aluminium oxide (CAS 1344-28-1)
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)
Glycerol (CAS 56-81-5)

US. California Proposition 65

This product is not subject to warning labeling under the California Proposition 65 regulation.

Inventory status


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	*	2
FLAMMABILITY		1
PHYSICAL HAZARD		0
PERSONAL PROTECTION		



Disclaimer

The information in the safety data sheet was written by Dell Tech Laboratories Ltd. (www.delltech.com) based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date 19-October-2022
Version No. 01
Effective date 19-October-2022
Further information Not available.