

SECTION 1: Identification**1.1. Product identifier**

Product form : Mixture
Product name : SONAX PROFILINE Surface Prep
Other means of identification : 02372410-755

1.2. Recommended use and restrictions on use

Recommended use : Laboratory chemicals

1.3. Supplier**Manufacturer**

Sonax GmbH
Münchener Strasse 75
D-86633 Neuburg/Donau
Germany
T 0049 84 31 53-0
info@sonax.com

Distributor

Vision Investments, LLC
17414 Tiller Court
Westfield, IN 46074
US
T 1-317-295-7056
info@sonaxusa.com

1.4. Emergency telephone number

Emergency number : GBK/Infotrac ID 91785, USA domestic - 1 800 535 5053, International - (001) 352 323

SECTION 2: Hazard identification**2.1. Classification of the substance or mixture****Classification (GHS CA/US)**

Flammable liquids Category 3

Flammable liquid and vapor

2.2. GHS Label elements, including precautionary statements**GHS CA/US labeling**

Hazard pictograms (GHS CA/US)

:



Signal word (GHS CA/US)

: Warning

Hazard statements (GHS CA/US)

: Flammable liquid and vapor

Precautionary statements (GHS CA/US)

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep container tightly closed.
Ground and bond container and receiving equipment.
Use explosion-proof electrical, ventilating, lighting equipment.
Use only non-sparking tools.
Take action to prevent static discharges.
Wear protective gloves, protective clothing, eye protection, face protection.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
In case of fire: Use media other than water to extinguish.
Store in a well-ventilated place. Keep cool
Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national or international regulation.

SONAX PROFILINE Surface Prep

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 10/24/2024 Version: 1.0

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS CA/US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Ethyl alcohol	CAS-No.: 64-17-5	30 - 60

Comments

: CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with the amended HPR as of April 2018.
US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water . Get immediate medical advice and attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation persists.
First-aid measures after ingestion	: Do not induce vomiting. If vomiting occurs have person lean forward. Never give anything by mouth to an unconscious person. Call a poison center or a doctor if you feel unwell.
First-aid measures general	: If you feel unwell, seek medical advice (show the label where possible). Medical personnel should be made aware of substance(s) involved and take measures for self protection. Show this safety data sheet to the doctor in attendance. Avoid contact with skin and eyes. Keep out of the reach of children.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: Prolonged inhalation may be harmful.
Symptoms/effects after skin contact	: Avoid contact with skin. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
Symptoms/effects after eye contact	: Direct contact with eyes may cause temporary irritation.
Symptoms/effects after ingestion	: May cause stomach distress, nausea or vomiting.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	: Symptoms may be delayed. Treat symptomatically.
-----------------------------------	---

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Water spray. Fire-extinguishing powder. Alcohol-resistant foam. Carbon dioxide.
------------------------------	---

SONAX PROFILINE Surface Prep

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 10/24/2024 Version: 1.0

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

5.3. Specific hazards arising from the hazardous product

Fire hazard : Flammable liquid and vapor. During fire, gases hazardous to health may be formed. In case of fire or explosion do not breathe fumes.
Explosion hazard : No direct explosion hazard.
Hazardous decomposition products in case of fire : May include and are not limited to: oxides of carbon.

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Move containers from fire area if it can be done without personal risk.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Keep unnecessary personnel away. For personal protection, see section 8 of the SDS. In the event of a significant spillage : Notify authorities if product enters sewers or public waters.

6.2. Methods and materials for containment and cleaning up

For containment : Stop leaks if it can be done without personal risk. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up : Notify authorities if product enters sewers or public waters. Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). Clean contaminated surfaces with an excess of water.
Other information : This material and its container must be disposed of in a safe way, and as per local legislation.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Avoid contact with skin, eyes and clothing. Avoid breathing vapors, mist. Do not taste or swallow. Wear personal protective equipment. Ensure good ventilation of the work station. Handle and open container with care.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of reach of children. Store tightly closed in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Store away from foodstuffs.
Storage temperature : 20 °C (68 °F)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

SONAX PROFILINE Surface Prep

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 10/24/2024 Version: 1.0

Ethyl alcohol (64-17-5)	
Canada (Alberta) - Occupational Exposure Limits	
OEL TWA	1880 mg/m ³ 1000 ppm
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
VECD (OEL STEV)	1000 ppm
Notations and remarks	C3
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
OEL STEL	1000 ppm
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
OEL STEL	1000 ppm
Notations and remarks	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2024
Canada (New Brunswick) - Occupational Exposure Limits	
OEL STEL	1000 ppm
Notations and remarks	URT irr
Regulatory reference	ACGIH 2024
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
OEL STEL	1000 ppm
Notations and remarks	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2024
Canada (Nova Scotia) - Occupational Exposure Limits	
OEL STEL	1000 ppm
Notations and remarks	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2024
Canada (Nunavut) - Occupational Exposure Limits	
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)

SONAX PROFILINE Surface Prep

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 10/24/2024 Version: 1.0

Ethyl alcohol (64-17-5)	
Canada (Ontario) - Occupational Exposure Limits	
OEL TWAEV	1000 ppm
Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
Canada (Prince Edward Island) - Occupational Exposure Limits	
OEL STEL	1000 ppm
Notations and remarks	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2024
Canada (Saskatchewan) - Occupational Exposure Limits	
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
Canada (Yukon) - Occupational Exposure Limits	
OEL TWA	1900 mg/m³
	1000 ppm
OEL STEL	1900 mg/m³
	1000 ppm
Regulatory reference	Occupational Health Regulations, YOIC 1986D/164
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL STEL	1000 ppm
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA	1900 mg/m³
	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
IDLH	3300 ppm (10% LEL)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	1900 mg/m³
	1000 ppm

8.2. Appropriate engineering controls

Appropriate engineering controls	: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Environmental exposure controls	: Avoid release to the environment.

SONAX PROFILINE Surface Prep

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 10/24/2024 Version: 1.0

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear protective gloves. Confirm with a reputable supplier first.

Eye protection:

Wear eye protection

Skin and body protection:

Wear suitable protective clothing. As required by employer code.

Respiratory protection:

Where exposure guideline levels may be exceeded, use an approved NIOSH respirator.
Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: No data available
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
pH	: 6.5 – 7.5
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 78 °C (172.4 °F)
Flash point	: 24 °C (75.2 °F)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable liquid and vapor
Vapor pressure	: 59 hPa
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 10 – 15 mm²/s
Explosive properties	: Not explosive.
Oxidizing properties	: Not oxidising.
Explosion limits	: Lower explosion limit: 3.5 vol % Upper explosion limit: 15 vol %

9.2. Other information

No additional information available

SONAX PROFILINE Surface Prep

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 10/24/2024 Version: 1.0

SECTION 10: Stability and reactivity

Reactivity	: Flammable liquid and vapor.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. Do not mix with other chemicals.
Incompatible materials	: Strong oxidizing agents.
Hazardous decomposition products	: May include and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Ethyl alcohol (64-17-5)	
LD50 oral rat	7060 mg/kg (Source: NLM_CIP)
LD50 oral	8300 mg/kg body weight Animal: mouse
LD50 dermal rabbit	> 15800 mg/kg body weight (Rabbit, Experimental value, Dermal)
LC50 Inhalation - Rat	133.8 mg/l/4h
LC50 Inhalation - Rat (Dust/Mist)	≥ mg/l/4h
LC50 Inhalation - Rat (Vapours)	133.8 mg/l/4h
ATE CA (oral)	7060 mg/kg body weight
ATE CA (vapors)	133.8 mg/l/4h
ATE CA (dust,mist)	133.8 mg/l/4h

Skin corrosion/irritation	: Not classified.
Serious eye damage/irritation	: Not classified.

SONAX PROFILINE Surface Prep	
Specific concentration limit	Eye irritant: C ≥ 50%

Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Ethyl alcohol (64-17-5)	
IARC group	1 - Carcinogenic to humans,(in alcoholic beverages)

Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

SONAX PROFILINE Surface Prep

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 10/24/2024 Version: 1.0

Ethyl alcohol (64-17-5)	
NOAEL (subchronic,oral,animal/male,90 days)	< 9700 mg/kg body weight Animal: mouse, Animal sex: male, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
NOAEL (subchronic,oral,animal/female,90 days)	> 9400 mg/kg body weight Animal: mouse, Animal sex: female, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)

Aspiration hazard	: Not classified
Likely routes of exposure	: Skin and eye contact. Ingestion. Inhalation.
Symptoms/effects after inhalation	: Prolonged inhalation may be harmful.
Symptoms/effects after skin contact	: Avoid contact with skin. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
Symptoms/effects after eye contact	: Direct contact with eyes may cause temporary irritation.
Symptoms/effects after ingestion	: May cause stomach distress, nausea or vomiting.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: See below for route-specific details.
Hazardous to the aquatic environment, short-term (acute)	: Not classified.
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Ethyl alcohol (64-17-5)	
LC50 - Fish [1]	12 – 16 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: EPA)
LC50 - Fish [2]	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
EC50 - Crustacea [1]	9268 – 14221 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 - Crustacea [2]	2 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 72h - Algae [1]	275 mg/l (Equivalent or similar to OECD 201, Chlorella vulgaris, Static system, Fresh water, Experimental value, Growth rate)
NOEC (chronic)	9.6 mg/l Test organisms (species): Daphnia magna Duration: '9 d'

12.2. Persistence and degradability

Ethyl alcohol (64-17-5)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.8 – 0.967 g O ₂ /g substance
Chemical oxygen demand (COD)	1.7 g O ₂ /g substance
ThOD	2.1 g O ₂ /g substance

12.3. Bioaccumulative potential

Ethyl alcohol (64-17-5)	
Bioaccumulative potential	Not bioaccumulative.
Partition coefficient n-octanol/water (Log Pow)	-0.35 (at 24 °C (at pH 7.4)

SONAX PROFILINE Surface Prep

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 10/24/2024 Version: 1.0

12.4. Mobility in soil

Ethyl alcohol (64-17-5)	
Surface tension	22.31 mN/m (20 °C, 100 %)
Ecology - soil	Highly mobile in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.2 (log Koc, Experimental value)

12.5. Other adverse effects

Ozone : Not classified



SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	: Dispose of the material collected according to regulations.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling, disposal or collection.
Additional information	: Flammable vapors may accumulate in the container.

SECTION 14: Transport information

In accordance with TDG / DOT

TDG	DOT
14.1. UN number	
UN1170	UN1170
14.2. Proper Shipping Name	
ETHANOL SOLUTION	Ethanol solutions
Transport document description	
UN1170 ETHANOL SOLUTION, 3, III	UN1170 Ethanol solutions, 3, III
14.3. Transport hazard class(es)	
3	3
	
14.4. Packing group	
III	III
14.5. Environmental hazards	
Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available	

SONAX PROFILINE Surface Prep

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 10/24/2024 Version: 1.0

14.6. Special precautions for user

TDG

UN-No. (TDG) : UN1170
Excepted quantities (TDG) : E1
Emergency Response Guide (ERG) Number : 127

DOT

UN-No.(DOT) : UN1170
DOT Special Provisions (49 CFR 172.102) : 24 - Alcoholic beverages containing more than 70 percent alcohol by volume must be transported as materials in Packing Group II. Alcoholic beverages containing more than 24 percent but not more than 70 percent alcohol by volume must be transported as materials in Packing Group III.
B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.
IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).
T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx) : 4b;150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

All components of this product are present on DSL

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

SONAX PROFILINE Surface Prep

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 10/24/2024 Version: 1.0

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

Issue date : 10/24/2024

Other information : For an updated SDS, please contact the supplier or manufacturer listed on the first page of the document.

The information in the safety data sheet was written by Dell Tech Laboratories Ltd. (www.delltech.com) based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.