

SAFETY DATA SHEET

1. Identification

SONAX PROFILINE UltimateCut Product identifier

Other means of identification

02390000, 02391410, 02393000, 02395000 Synonyms

Recommended use Car Care Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Sonax GmbH

Address Münchener Strasse 75

D-86633 Neuburg/Donau

Germany

Telephone Phone: 0049 84 31 53-0

info@sonax.com E-mail

Emergency CONTACT (24 GBK/Infotrac ID 91785: **Emergency phone number**

(USA domestic) 1 800 535 5053

or international (001) 352 323

Vision Investments, LLC Supplier

17414 Tiller Court Westfield, IN 46074 US Email: info@sonaxusa.com Phone: 1-317-295-7056

2. Hazard identification

Physical hazards Not classified. Health hazards Not classified. **Environmental hazards** Not classified. WHMIS 2015 defined hazards Not classified

Label elements

Hazard symbol None. Signal word None

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Wash hands after handling. Response

Store away from incompatible materials. Storage

Dispose of waste and residues in accordance with local authority requirements. Disposal

WHMIS 2015: Health Hazard(s)

not otherwise classified

(HHNOC)

None known

WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC)

None known

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information

None.

3. Composition/Information on ingredients

Mixture

| Chemical name | Common name and synonyms | CAS number | % |
|-----------------|--------------------------|------------|---------|
| Aluminium oxide | | 1344-28-1 | 10 - 30 |

#35492 Page: 1 of 11 Issue date 19-October-2022

| Chemical name | Common name and synonyms | CAS number | % |
|--|---|-----------------------------------|-------------------------|
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based | | 72623-86-0 | 5 - 10 |
| 1,2-Propanediol | | 57-55-6 | 1 - 5 |
| Distillates (petroleum), hydrotromiddle | eated | 64742-46-7 | 1 - 5 |
| Distillates (petroleum), light hydrotreated | | 64742-47-8 | 1 - 5 |
| Glycerol | | 56-81-5 | 1 - 5 |
| All concentrations are in percent l | by weight unless ingredient is a gas. Gas conce | entrations are in percent by volu | ume. |
| Composition comments | CANADA GHS: The exact percentage (concernsected). US GHS: The exact percentage (concentration secret in accordance with paragraph (i) of §1 | on) of composition has been w | |
| | 4. First-aid measures | 3 | |
| Inhalation | If symptoms develop move victim to fresh air | . If symptoms persist, obtain m | nedical attention. |
| Skin contact | Flush with cool water. Wash with soap and w | ater. Obtain medical attention | if irritation persists. |
| Eye contact | Flush with cool water. Remove contact lense attention if irritation persists. | es, if applicable, and continue f | ushing. Obtain medical |

reduce risk of aspiration. Never give anything by mouth if victim is unconscious or is convulsing. Obtain medical attention. Most important symptoms/effects, acute and

Direct contact with eyes may cause temporary irritation.

delayed Indication of immediate medical attention and special

Treat patient symptomatically.

treatment needed General information

Ingestion

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children.

Rinse mouth. Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to

5. Fire-fighting measures Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide. Not available.

Unsuitable extinguishing media

During fire, gases hazardous to health may be formed.

the chemical Special protective equipment and precautions for firefighters

Specific hazards arising from

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods General fire hazards Hazardous combustion products

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

May include and are not limited to: Oxides of carbon.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk, Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Do not discharge into lakes, streams, ponds or public waters.

7. Handling and storage

Wash thoroughly after handling. When using do not eat or drink.

Conditions for safe storage,

Store in original tightly closed container.

including any incompatibilities Store away from incompatible materials (see Section 10 of the SDS).

Keep out of reach of children.

8. Exposure controls/Personal protection

| $\Omega_{\alpha\alpha}$ | national | exposure | limita |
|-------------------------|----------|----------|----------|
| Occu | pationai | exposure | IIIIIIII |

Components

| Components | Туре | Value | Form | |
|---|------|-----------|---------|--|
| Aluminium oxide (CAS 1344-28-1) | TWA | 10 mg/m3 | | |
| Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) | STEL | 10 mg/m3 | Mist. | |
| | TWA | 5 mg/m3 | Mist. | |
| Distillates (petroleum), light hydrotreated (CAS 64742-47-8) | TWA | 200 mg/m3 | Vapour. | |
| Glycerol (CAS 56-81-5) | TWA | 10 mg/m3 | Mist. | |

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

| Components | Туре | Value | Form |
|---|------|---------------------|---------------------------|
| Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) | TWA | 1 mg/m3 | Mist. |
| Distillates (petroleum), light hydrotreated (CAS 64742-47-8) | TWA | 200 mg/m3 | Non-aerosol. |
| Glycerol (CAS 56-81-5) | TWA | 3 mg/m3 10 mg/m3 | Respirable mist. Mist. |

Canada, Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

| odilada. Mailitoba OLLS (fleg. 217/2000, The Workplace Salety And Fleatili Act) | | | |
|--|------|---------|---------------------|
| Components | Туре | Value | Form |
| Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) | TWA | 5 mg/m3 | Inhalable fraction. |
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0) | TWA | 5 mg/m3 | Inhalable fraction. |

Canada. New Brunswick OELs: Threshold Limit Values (TLVs) Based on the 1991 and 1997 ACGIH TLVs and BEIs Publication (New Brunswick Regulation 91-191), as amended

Form

Value

| Aluminium oxide (CAS 1344-28-1) | TWA | 10 mg/m3 | |
|---|------|----------|-------|
| Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) | STEL | 10 mg/m3 | Mist. |
| | TWA | 5 mg/m3 | Mist. |
| Glycerol (CAS 56-81-5) | TWA | 10 mg/m3 | Mist. |

Type

| Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) | | | |
|--|------|-----------|---------------------|
| Components | Туре | Value | Form |
| 1,2-Propanediol (CAS 57-55-6) | TWA | 155 mg/m3 | Vapour and aerosol. |
| | | 10 mg/m3 | Aerosol |
| | | 50 ppm | Vapour and aerosol. |
| Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) | TWA | 5 mg/m3 | Inhalable fraction. |

| Canada. Ontario OELs. (Control of Expos Components | Type | Value | Form |
|--|-------------------------------------|------------------------------------|----------------------------|
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0) | TWA | 5 mg/m3 | Inhalable fraction. |
| Canada. Quebec OELs. (Ministry of Labo Components | r - Regulation respecting o Type | ccupational health and sa Value | afety) Form |
| Aluminium oxide (CAS | TWA | 10 mg/m3 | Total dust. |
| 1344-28-1) | IWA | To mg/ms | Total dust. |
| Distillates (petroleum), nydrotreated middle (CAS 64742-46-7) | STEL | 10 mg/m3 | Mist. |
| | TWA | 5 mg/m3 | Mist. |
| Glycerol (CAS 56-81-5) | TWA | 10 mg/m3 | Mist. |
| Canada. Saskatchewan OELs (Occupatio Components | onal Health and Safety Reg Type | ulations, 1996, Table 21) Value | Form |
| Aluminium oxide (CAS | 15 minute | 20 mg/m3 | |
| 1344-28-1) | | | |
| | 8 hour | 10 mg/m3 | |
| Distillates (petroleum), nydrotreated middle (CAS 64742-46-7) | 15 minute | 10 mg/m3 | |
| | 8 hour | 5 mg/m3 | |
| Distillates (petroleum), light nydrotreated (CAS 64742-47-8) | 15 minute | 250 mg/m3 | Vapour. |
| | 8 hour | 200 mg/m3 | Vapour. |
| Glycerol (CAS 56-81-5) | 15 minute | 20 mg/m3 | Mist. |
| | 8 hour | 10 mg/m3 | Mist. |
| US. OSHA Table Z-1 Limits for Air Contai Components | minants (29 CFR 1910.1000 Type |) Value | Form |
| Aluminium oxide (CAS | PEL | 5 mg/m3 | Respirable fraction. |
| (344-28-1) | | _ | |
| Distillator (notraloum) | PEL | 15 mg/m3 | Total dust. Mist. |
| Distillates (petroleum), nydrotreated middle (CAS 64742-46-7) | PEL | 5 mg/m3 | MIST. |
| Glycerol (CAS 56-81-5) | PEL | 5 mg/m3 | Respirable fraction. |
| | | 15 mg/m3 | Total dust. |
| US. OSHA Table Z-3 (29 CFR 1910.1000) Components | Туре | Value | Form |
| Aluminium oxide (CAS | TWA | 5 mg/m3 | Respirable fraction. |
| 1344-28-1) | | · | |
| | | 15 mg/m3 50 Mppcf | Total dust. Total dust. |
| | | 15 Mppcf | Respirable fraction. |
| Glycerol (CAS 56-81-5) | TWA | 5 mg/m3 | Respirable fraction. |
| , | | 15 mg/m3 | Total dust. |
| | | 50 Mppcf | Total dust. |
| | | 15 Mppcf | Respirable fraction. |
| US. ACGIH Threshold Limit Values | Typo | Value | Form |
| Components | Type TWA | | Inhalable fraction. |
| Distillatos (potroloum) | IVVA | 5 mg/m3 | пппатарте тгастоп. |
| Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) | | | |

US. NIOSH: Pocket Guide to Chemical Hazards Form Value Components Distillates (petroleum), STEL 10 mg/m3 Mist. hydrotreated middle (CAS 64742-46-7) **TWA** 5 mg/m3 Mist. Distillates (petroleum), light **TWA** 100 mg/m3 hydrotreated (CAS 64742-47-8) US. Workplace Environmental Exposure Level (WEEL) Guides Components Value Form Type 1,2-Propanediol (CAS **TWA** Aerosol 10 mg/m3

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines

57-55-6)

Canada - Alberta OELs: Skin designation

Distillates (petroleum), light hydrotreated (CAS Can be absorbed through the skin.

64742-47-8)

Canada - British Columbia OELs: Skin designation

Distillates (petroleum), light hydrotreated (CAS Can be absorbed through the skin.

64742-47-8)

Canada - Saskatchewan OELs: Skin designation

Distillates (petroleum), light hydrotreated (CAS Can be absorbed through the skin.

64742-47-8)

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Not normally required.

Skin protection

Hand protection Rubber gloves. Confirm with a reputable supplier first.

Wear appropriate chemical resistant clothing. Other

Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respiratory protection

Thermal hazards Not available.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. Form Liquid. Colour White Odour Solvent-like Not available. Odour threshold Not available. pН Not available. Melting point/freezing point

100 - 310 °C (212 - 590 °F) Initial boiling point and boiling

range

Not available. Specific gravity Flash point Not available. Not available. **Evaporation rate** Flammability (solid, gas) Not flammable Upper/lower flammability or explosive limits

Flammability limit - lower (%)

Not available.

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available. Not available. Explosive limit - upper

(%)

Not available. Vapour pressure Vapour density Not available. Relative density Not available. Not available. Solubility(ies) Not available. Partition coefficient

(n-octanol/water)

Auto-ignition temperature Not available. Not available. **Decomposition temperature** Not available. Viscosity

Other information

Pour point Not available.

1.00 - 1.20 g/cm3 (20 °C / 68 °F) Density

Explosive properties Not explosive. Kinematic viscosity $> 20.5 \text{ mm}^2/\text{s}$ 40 °C (104 °F) Kinematic viscosity

temperature

Oxidising properties Not oxidising.

10. Stability and reactivity

No dangerous reaction known under conditions of normal use.

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Possibility of hazardous

reactions

Chemical stability

Material is stable under normal conditions.

Conditions to avoid Do not mix with other chemicals.

Incompatible materials None when used and stored according to label directions.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Inhalation. Ingestion. Skin contact. Eye contact. Routes of exposure

Information on likely routes of exposure

Ingestion May cause stomach distress, nausea or vomiting.

Prolonged inhalation may be harmful. Inhalation

Skin contact No adverse effects due to skin contact are expected. Eye contact Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics There are no hazards associated with this product in normal use.

Information on toxicological effects

Acute toxicity See below.

Species **Test Results** Components

1,2-Propanediol (CAS 57-55-6)

Acute Dermal

LD50

Rabbit > 2000 mg/kg, 24 Hours, ECHA

Inhalation

Rabbit LC50 > 317042 mg/m3, 2 Hours, ECHA

Oral

LD50 Rat 22000 mg/kg, ECHA

Aluminium oxide (CAS 1344-28-1)

Acute

Dermal

LD50 Not available

| Components | Species | Test Results |
|---|---|--------------------------------|
| Inhalation | | |
| LC50 | Rat | > 2.3 mg/L, 4 Hours, ECHA |
| | | 7.6 mg/L, 1 Hours |
| Oral | | |
| LD50 | Rat | > 2000 mg/kg, ECHA |
| Distillates (petroleum), hydrotreate Acute | ed middle (CAS 64742-46-7) | |
| Dermal | | |
| LD50 | Rabbit | > 2000 mg/kg, 24 Hours, ECHA |
| Inhalation | | |
| LC50 | Rat | 7640 mg/m3, 4 Hours, ECHA |
| | | 4.6 mg/L, 4 Hours, ECHA |
| Oral | | |
| LD50 | Rat | > 5000 mg/kg, ECHA |
| Distillates (petroleum), light hydrot | reated (CAS 64742-47-8) | |
| Acute | | |
| <i>Dermal</i> LD50 | Rabbit | > 2000 mg/kg, 24 Hours, ECHA |
| | nabbit | > 2000 Hig/kg, 24 Hours, EOHA |
| Inhalation LC50 | Rat | > 5.3 mg/L, 4 Hours, ECHA |
| Oral | Tidi | > 0.0 Hig/E, 4 Hours, 2011/1 |
| LD50 | Rat | > 5000 mg/kg, ECHA |
| Glycerol (CAS 56-81-5) | | |
| Acute | | |
| Dermal | | |
| LD50 | Guinea pig | 56750 mg/kg, ECHA |
| Inhalation | | |
| LC50 | Rat | 275000 mg/m³, 4 hours, ECHA |
| Oral | | |
| LD50 | Rat | 11500 mg/kg, ECHA |
| | 30, hydrotreated neutral oil-based (CAS 72623-86-0) | |
| Acute | | |
| <i>Dermal</i> LD50 | Rabbit | > 2000 mg/kg, 24 Hours, ECHA |
| | Habbit | > 2000 Hig/kg, 24 Hours, LOTIA |
| Inhalation LC50 | Rat | > 5.2 mg/L, 4 Hours, ECHA |
| Oral | | 5 6.2 mg/2, 1116a16, 261111 |
| LD50 | Rat | 5000 mg/kg, ECHA |
| Skin corrosion/irritation | Prolonged skin contact may cause temporary irritation | on. |
| Exposure minutes | Not available. | |
| Erythema value | Not available. | |
| Oedema value | Not available. | |
| Serious eye damage/eye irritation | Direct contact with eyes may cause temporary irritat | ion. |
| Corneal opacity value | Not available. | |
| Iris lesion value | Not available. | |
| Conjunctival reddening value | Not available. | |
| Conjunctival oedema value | Not available. | |
| Recover days | Not available. | |
| Respiratory or skin sensitisation | | |
| Canada - Alberta OELs: Irrita | | |
| Glycerol (CAS 56-81-5) | Irritant | |

Respiratory sensitisation Not a respiratory sensitizer.

This product is not expected to cause skin sensitisation. Skin sensitisation

No data available to indicate product or any components present at greater than 0.1% are Mutagenicity

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

ACGIH Carcinogens

Lubricating oils (petroleum), C15-30, hydrotreated neutral A2 Suspected human carcinogen.

oil-based (CAS 72623-86-0)

Canada - Manitoba OELs: carcinogenicity

Lubricating oils (petroleum), C15-30, hydrotreated neutral Suspected human carcinogen.

oil-based (CAS 72623-86-0)

IARC Monographs. Overall Evaluation of Carcinogenicity

Volume 33, Supplement 7 - 3 Not classifiable as to carcinogenicity Distillates (petroleum), hydrotreated middle (CAS

64742-46-7) to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not listed.

US NTP Report on Carcinogens: Known carcinogen

Lubricating oils (petroleum), C15-30, hydrotreated neutral Known To Be Human Carcinogen.

oil-based (CAS 72623-86-0)

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Teratogenicity Specific target organ toxicity -

Not available. Not classified.

single exposure

Specific target organ toxicity repeated exposure

Not classified.

Not an aspiration hazard. Aspiration hazard

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

See below **Ecotoxicity**

Ecotoxicological data

Test Results Components **Species**

1,2-Propanediol (CAS 57-55-6)

Crustacea EC50 Daphnia 10000 mg/L, 48 Hours

Aquatic

Crustacea EC50 Water flea (Daphnia magna) > 10000 mg/L, 48 hours

LC50 Fish Fathead minnow (Pimephales promelas) 710 mg/L, 96 hours

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

Aquatic

Fish LC50 Rainbow trout, donaldson trout 2.9 mg/L, 96 hours

(Oncorhynchus mykiss)

Glycerol (CAS 56-81-5)

Aquatic

Fish LC50 Rainbow trout, donaldson trout 51000 - 57000 mg/L, 96 hours

(Oncorhynchus mykiss)

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0)

Crustacea FC50 Daphnia 1000 mg/L, 48 Hours

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

No data available. Mobility in soil Mobility in general Not available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations Dispose in accordance with all applicable regulations. Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

Transport of Dangerous Goods (TDG) Proof of Classification

Classification Method: Classified as per Part 2, Sections 2.1 - 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.

U.S. Department of Transportation (DOT)

Not regulated as dangerous goods.

Transportation of Dangerous Goods (TDG - Canada)

Not regulated as dangerous goods.

15. Regulatory information

1 TONNES

Canadian federal regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Distillates (petroleum), light hydrotreated (CAS

64742-47-8)

Canada Priority Substances List (Second List): Listed substance

Aluminium oxide (CAS 1344-28-1) Glycerol (CAS 56-81-5) Listed.

Export Control List (CEPA 1999, Schedule 3)

Not listed

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

WHMIS 2015 Exemptions

Not applicable

US Federal regulations

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Distillates (petroleum), light hydrotreated (CAS

Listed.

64742-47-8)

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely

hazardous substance

Nο

SARA 311/312 Hazardous chemical

SARA 313 (TRI reporting)

Chemical name CAS number % by wt. Aluminium oxide 1344-28-1 10 - 30

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

US state regulations

US - California Hazardous Substances (Director's): Listed substance

Aluminium oxide (CAS 1344-28-1)

Listed.

Distillates (petroleum), hydrotreated middle (CAS Listed. 64742-46-7)

US - Illinois Chemical Safety Act: Listed substance

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

US - Louisiana Spill Reporting: Listed substance

Distillates (petroleum), light hydrotreated (CAS Listed. 64742-47-8)

US - Minnesota Haz Subs: Listed substance

1,2-Propanediol (CAS 57-55-6)

Aluminium oxide (CAS 1344-28-1)

Distillates (petroleum), hydrotreated middle (CAS Listed. 64742-46-7)

Listed.

Glycerol (CAS 56-81-5) Listed.

US - Texas Effects Screening Levels: Listed substance

1,2-Propanediol (CAS 57-55-6)

Aluminium oxide (CAS 1344-28-1)

Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

Listed.

Glycerol (CAS 56-81-5)

Listed.

Lubricating oils (petroleum), C15-30, hydrotreated neutral Listed.

oil-based (CAS 72623-86-0)

US. Massachusetts RTK - Substance List

Aluminium oxide (CAS 1344-28-1)

Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Glycerol (CAS 56-81-5)

US. New Jersey Worker and Community Right-to-Know Act

1,2-Propanediol (CAS 57-55-6)

Aluminium oxide (CAS 1344-28-1)

Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Glycerol (CAS 56-81-5)

US. Pennsylvania Worker and Community Right-to-Know Law

1,2-Propanediol (CAS 57-55-6)

Aluminium oxide (CAS 1344-28-1)

Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Glycerol (CAS 56-81-5)

US. Rhode Island RTK

1,2-Propanediol (CAS 57-55-6)

Aluminium oxide (CAS 1344-28-1)

Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

Glycerol (CAS 56-81-5)

US. California Proposition 65

This product is not subject to warning labeling under the California Proposition 65 regulation.

Inventory status


| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|---|------------------------|
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information







Disclaimer The information in the safety data sheet was written by Dell Tech Laboratories Ltd.

(www.delltech.com) based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date 19-October-2022

Version No. 01

Effective date 19-October-2022
Further information Not available.