

## 1. Identification

<b>Product identifier</b>	<b>SONAX PROFILINE Ceramic Coating CC Plastic+Rubber</b>	
<b>Other means of identification</b>	Article number: 02410000-755	
<b>Recommended use</b>	Consumer uses: Private households / general public / consumers Professional uses Coating	
<b>Recommended restrictions</b>	None known.	
<b>Manufacturer/Importer/Supplier/Distributor information</b>		
<b>Manufacturer</b>		
<b>Company name</b>	Sonax GmbH	
<b>Address</b>	Münchener Strasse 75 D-86633 Neuburg/Donau Germany	
<b>Telephone</b>	Phone:	0049 84 31 53-0
<b>E-mail</b>	Not available.	
<b>Emergency phone number</b>	Emergency Contact (24h)	GBK/Infotrac ID 91785: (USA domestic) 1 800 535 5053 or international (001) 352 323
<b>Supplier</b>	Vision Investments, LLC 17414 Tiller Court Westfield, IN 46074 US Email: info@sonaxusa.com Phone: 1-317-295-7056	

## 2. Hazard identification

<b>Physical hazards</b>	Flammable liquids	Category 3
<b>Health hazards</b>	Reproductive toxicity	Category 1B
<b>Environmental hazards</b>	Not classified.	
<b>WHMIS 2015 defined hazards</b>	Not classified	
<b>Label elements</b>		



<b>Signal word</b>	Danger
<b>Hazard statement</b>	Flammable liquid and vapour. May damage fertility or the unborn child.
<b>Precautionary statement</b>	
<b>Prevention</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves, protective clothing, eye protection and face protection.
<b>Response</b>	IF exposed or concerned: Get medical attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. In case of fire: Use appropriate media to extinguish.
<b>Storage</b>	Store in a well-ventilated place. Keep cool. Store locked up.
<b>Disposal</b>	Dispose of container in accordance with local, regional, national and international regulations.
<b>WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC)</b>	None known
<b>WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC)</b>	None known

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

---

### 3. Composition/Information on ingredients

---

#### Mixture

Chemical name	Common name and synonyms	CAS number	%
Methanol		67-56-1	0.1 - 1
Toluene		108-88-3	0.1 - 1

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**Composition comments** CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret.

US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

---

### 4. First-aid measures

---

<b>Inhalation</b>	Move to fresh air. If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
<b>Skin contact</b>	Flush with cool water. Wash with soap and water. Obtain medical attention if irritation persists.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth if victim is unconscious or is convulsing. Get medical attention if symptoms occur.
<b>Most important symptoms/effects, acute and delayed</b>	Direct contact with eyes may cause temporary irritation. Methanol is readily and rapidly absorbed at all exposure routes and is toxic by all routes. Methanol may cause irritation of the mucosa, as well as nausea, vomiting, headaches, vertigo and visual disorders, including blindness (irreversible damage to the optic nerve), acidosis, spasms, narcosis and coma. There may be a delay in the onset of these effects after exposure.
<b>Indication of immediate medical attention and special treatment needed</b>	Symptoms may be delayed. Treat patient symptomatically.
<b>General information</b>	If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

---

### 5. Fire-fighting measures

---

<b>Suitable extinguishing media</b>	Foam. Carbon dioxide (CO <sub>2</sub> ). Dry chemical powder. Water spray. Sand.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire-fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	Flammable liquid and vapour.
<b>Hazardous combustion products</b>	May include and are not limited to: Carbon monoxide and carbon dioxide. Methanol. Ethanol. Flammable gases/fumes. Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C through oxidation.

---

### 6. Accidental release measures

---

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	---

**Methods and materials for containment and cleaning up**

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

**Environmental precautions**

Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

**Precautions for safe handling**

Avoid contact with skin and eyes. Avoid breathing vapours or mists. Do not taste or swallow. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

**Conditions for safe storage, including any incompatibilities**

Keep out of reach of children. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Keep in original container. Keep container tightly closed in a cool, dry and well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). Store away from foodstuffs. Recommended storage temperature: 20 °C / 68 °F

## 8. Exposure controls/Personal protection

**Occupational exposure limits****Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)**

Components	Type	Value
Methanol (CAS 67-56-1)	STEL	328 mg/m3 250 ppm
	TWA	262 mg/m3 200 ppm
	TWA	188 mg/m3 50 ppm

**Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)**

Components	Type	Value
Methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

**Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)**

Components	Type	Value
Methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

**Canada. New Brunswick Regulation 91-191, as amended**

Components	Type	Value
Methanol (CAS 67-56-1)	STEL	328 mg/m3 250 ppm
	TWA	262 mg/m3 200 ppm
	TWA	188 mg/m3 50 ppm

**Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)**

Components	Type	Value
Methanol (CAS 67-56-1)	STEL	250 ppm

**Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)**

Components	Type	Value
	TWA	200 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

**Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)**

Components	Type	Value
Methanol (CAS 67-56-1)	STEL	328 mg/m3 250 ppm
	TWA	262 mg/m3 200 ppm
Toluene (CAS 108-88-3)	TWA	188 mg/m3 50 ppm

**Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 2020. S-15.1 Reg. 10. Table 18)**

Components	Type	Value
Methanol (CAS 67-56-1)	15 minute	250 ppm
	8 hour	200 ppm
Toluene (CAS 108-88-3)	15 minute	60 ppm
	8 hour	50 ppm

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
Methanol (CAS 67-56-1)	PEL	260 mg/m3 200 ppm

**US. OSHA Table Z-2 (29 CFR 1910.1000)**

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

**US. ACGIH Threshold Limit Values**

Components	Type	Value
Methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
Methanol (CAS 67-56-1)	STEL	325 mg/m3 250 ppm
	TWA	260 mg/m3 200 ppm
	TWA	375 mg/m3 100 ppm
Toluene (CAS 108-88-3)	STEL	560 mg/m3 150 ppm
	TWA	375 mg/m3 100 ppm

**Biological limit values**

**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Methanol (CAS 67-56-1)	15 mg/L	Methanol	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/L	Toluene	Urine	*
	0.02 mg/L	Toluene	Blood	*

\* - For sampling details, please see the source document.

**Exposure guidelines**

**Canada - Alberta OELs: Skin designation**

Methanol (CAS 67-56-1) Can be absorbed through the skin.  
Toluene (CAS 108-88-3) Can be absorbed through the skin.

<b>Canada - British Columbia OELs: Skin designation</b>	
Methanol (CAS 67-56-1)	Can be absorbed through the skin.
<b>Canada - Manitoba OELs: Skin designation</b>	
Methanol (CAS 67-56-1)	Danger of cutaneous absorption
<b>Canada - Ontario OELs: Skin designation</b>	
Methanol (CAS 67-56-1)	Can be absorbed through the skin.
<b>Canada - Quebec OELs: Skin designation</b>	
Methanol (CAS 67-56-1)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.
<b>Canada - Saskatchewan OELs: Skin designation</b>	
Methanol (CAS 67-56-1)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.
<b>US ACGIH Threshold Limit Values: Skin designation</b>	
Methanol (CAS 67-56-1)	Danger of cutaneous absorption
<b>US NIOSH Pocket Guide to Chemical Hazards: Skin designation</b>	
Methanol (CAS 67-56-1)	Can be absorbed through the skin.
<b>Appropriate engineering controls</b>	Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
<b>Individual protection measures, such as personal protective equipment</b>	
<b>Eye/face protection</b>	Wear safety glasses with side shields (or goggles).
<b>Skin protection</b>	
<b>Hand protection</b>	Wear appropriate chemical resistant gloves. Butyl rubber. Thickness: ≥ 0.5 mm Nitrile rubber. Thickness: ≥ 0.4 mm
<b>Other</b>	Wear suitable protective clothing.
<b>Respiratory protection</b>	Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).
<b>Thermal hazards</b>	Not available.
<b>General hygiene considerations</b>	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

---

## 9. Physical and chemical properties

---

<b>Appearance</b>	Liquid
<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Colour</b>	Colourless
<b>Odour</b>	Solvent-like. weak, Characteristic
<b>Odour threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	143 °C (289.4 °F)
<b>Specific gravity</b>	Not available.
<b>Flash point</b>	32.0 °C (89.6 °F)
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Flammable liquid and vapour.
<b>Upper/lower flammability or explosive limits</b>	
<b>Explosive limit - lower (%)</b>	3.5 %
<b>Explosive limit – upper (%)</b>	15 %
<b>Vapour pressure</b>	13.3 hPa
<b>Vapour density</b>	Not available.
<b>Relative density</b>	Not available.

<b>Solubility(ies)</b>	Not miscible or difficult to mix.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Pour point</b>	Not available.
<b>Density</b>	0.98 - 0.99 g/cm <sup>3</sup>
<b>Explosive properties</b>	Not explosive.
<b>Oxidising properties</b>	Not oxidising.

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Conditions to avoid</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point.
<b>Incompatible materials</b>	Strong oxidising agents.
<b>Hazardous decomposition products</b>	May include and are not limited to: Carbon monoxide and carbon dioxide. Methanol. Ethanol Flammable gases/fumes. Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C through oxidation.

## 11. Toxicological information

<b>Routes of exposure</b>	Inhalation.
<b>Information on likely routes of exposure</b>	
<b>Ingestion</b>	May cause stomach distress, nausea or vomiting.
<b>Inhalation</b>	Prolonged inhalation may be harmful.
<b>Skin contact</b>	Prolonged or repeated contact may dry skin and cause irritation.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.
<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Direct contact with eyes may cause temporary irritation.

### Information on toxicological effects

**Acute toxicity** See below.

Components	Species	Test Results
Methanol (CAS 67-56-1)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	17100 mg/kg, ECHA
<i>Inhalation</i>		
LC50	Cat	43.7 mg/L, 6 Hours, ECHA
<i>Oral</i>		
LD50	Rat	> 2528 mg/kg, ECHA
Toluene (CAS 108-88-3)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	25.7 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	5580 mg/kg, ECHA
<b>Skin corrosion/irritation</b>	Prolonged skin contact may cause temporary irritation.	
<b>Exposure minutes</b>	Not available.	
<b>Erythema value</b>	Not available.	

<b>Oedema value</b>	Not available.
<b>Serious eye damage/eye irritation</b>	Direct contact with eyes may cause temporary irritation.
<b>Corneal opacity value</b>	Not available.
<b>Iris lesion value</b>	Not available.
<b>Conjunctival reddening value</b>	Not available.
<b>Conjunctival oedema value</b>	Not available.
<b>Recover days</b>	Not available.
<b>Respiratory or skin sensitisation</b>	
<b>Respiratory sensitisation</b>	Not a respiratory sensitizer.
<b>Skin sensitisation</b>	This product is not expected to cause skin sensitisation.
<b>Mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Carcinogenicity</b>	Not classifiable as to carcinogenicity to humans.
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>	
Toluene (CAS 108-88-3)	Volume 47, Volume 71 - 3 Not classifiable as to carcinogenicity to humans.
<b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)</b>	
Not listed.	
<b>Reproductive toxicity</b>	May damage fertility or the unborn child.
<b>Teratogenicity</b>	Not available.
<b>Specific target organ toxicity - single exposure</b>	Not classified.
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.
<b>Aspiration hazard</b>	Not an aspiration hazard.
<b>Chronic effects</b>	Prolonged inhalation may be harmful.

---

## 12. Ecological information

---

<b>Ecotoxicity</b>	See below		
<b>Ecotoxicological data</b>			
<b>Components</b>		<b>Species</b>	<b>Test Results</b>
Methanol (CAS 67-56-1)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea ( <i>Daphnia magna</i> )	> 10000 mg/L, 48 hours
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> )	> 100 mg/L, 96 hours
Toluene (CAS 108-88-3)			
Algae	IC50	Algae	433 mg/L, 72 Hours
Crustacea	EC50	Daphnia	7.645 mg/L, 48 Hours
<b>Aquatic</b>			
Crustacea	EC50	Water flea ( <i>Daphnia magna</i> )	5.46 - 9.83 mg/L, 48 hours
Fish	LC50	Coho salmon, silver salmon ( <i>Oncorhynchus kisutch</i> )	8.11 mg/L, 96 hours
<b>Persistence and degradability</b>	No data is available on the degradability of any ingredients in the mixture.		
<b>Bioaccumulative potential</b>			
<b>Mobility in soil</b>	No data available.		
<b>Mobility in general</b>	Not available.		
<b>Other adverse effects</b>	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		

---

## 13. Disposal considerations

---

<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.

<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

## 14. Transport information

---

**Transport of Dangerous Goods (TDG) Proof of Classification** Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.

**U.S. Department of Transportation (DOT)**

**Basic shipping requirements:**

<b>UN number</b>	UN1993
<b>Proper shipping name</b>	Flammable liquids, n.o.s.
<b>Technical name</b>	Methyl triethoxysilane
<b>Hazard class</b>	3
<b>Packing group</b>	III
<b>Marine pollutant</b>	Yes

**Transportation of Dangerous Goods (TDG - Canada)**

**Basic shipping requirements:**

<b>UN number</b>	UN1993
<b>Proper shipping name</b>	FLAMMABLE LIQUID, N.O.S.
<b>Technical name</b>	Methyl triethoxysilane
<b>Hazard class</b>	3
<b>Packing group</b>	III
<b>Marine pollutant</b>	Yes

**DOT**



**TDG**




---

## 15. Regulatory information

---

**Canadian federal regulations** This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

**Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number**

Methanol (CAS 67-56-1)	1 TONNES
Toluene (CAS 108-88-3)	1 TONNES

**Export Control List (CEPA 1999, Schedule 3)**

Not listed.

**Greenhouse Gases**

Not listed.

**Precursor Control Regulations**

Toluene (CAS 108-88-3)	Class B
------------------------	---------

**WHMIS 2015 Exemptions** Not applicable



**US Federal regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Methanol (CAS 67-56-1) Listed.  
Toluene (CAS 108-88-3) Listed.

**SARA 304 Emergency release notification**

Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)**

Not listed.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**SARA 302 Extremely hazardous substance** No

**SARA 311/312 Hazardous chemical** Yes

**Classified hazard categories** Flammable (gases, aerosols, liquids, or solids)

**SARA 313 (TRI reporting)**

Not regulated.

**Other federal regulations****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Methanol (CAS 67-56-1)  
Toluene (CAS 108-88-3)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**US state regulations****US - California Hazardous Substances (Director's): Listed substance**

Methanol (CAS 67-56-1) Listed.  
Toluene (CAS 108-88-3) Listed.

**US - Illinois Chemical Safety Act: Listed substance**

Methanol (CAS 67-56-1)  
Toluene (CAS 108-88-3)

**US - Louisiana Spill Reporting: Listed substance**

Methanol (CAS 67-56-1) Listed.  
Toluene (CAS 108-88-3) Listed.

**US - Michigan Critical Materials Register: Parameter number**

Toluene (CAS 108-88-3)

**US - Minnesota Haz Subs: Listed substance**

Methanol (CAS 67-56-1) Listed.  
Toluene (CAS 108-88-3) Listed.

**US - North Carolina Toxic Air Pollutants: Listed substance**

Toluene (CAS 108-88-3)

**US - Texas Effects Screening Levels: Listed substance**

Methanol (CAS 67-56-1) Listed.  
Toluene (CAS 108-88-3) Listed.

**US - Washington Chemical of High Concern to Children: Listed substance**

Toluene (CAS 108-88-3)

**US. Massachusetts RTK - Substance List**

Methanol (CAS 67-56-1)  
Toluene (CAS 108-88-3)

**US. New Jersey Worker and Community Right-to-Know Act**

Methanol (CAS 67-56-1)  
Toluene (CAS 108-88-3)

**US. Pennsylvania Worker and Community Right-to-Know Law**

Methanol (CAS 67-56-1)  
Toluene (CAS 108-88-3)

**US. Rhode Island RTK**

Methanol (CAS 67-56-1)  
Toluene (CAS 108-88-3)

**US. California Proposition 65**

**⚠ WARNING:** This product can expose you to chemicals including Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**California Proposition 65 - CRT: Listed date/Developmental toxin**

Methanol (CAS 67-56-1)  
Toluene (CAS 108-88-3)

Listed: March 16, 2012  
Listed: January 1, 1991

**Inventory status**


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

**16. Other information**

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

<b>HEALTH</b>	/ 1
<b>FLAMMABILITY</b>	3
<b>PHYSICAL HAZARD</b>	0
<b>PERSONAL PROTECTION</b>	



**Disclaimer**

The information in the safety data sheet was written by Dell Tech Laboratories Ltd. ([www.delltech.com](http://www.delltech.com)) based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

**Issue date**

21-September-2023

**Version No.**

01

**Effective date**

21-September-2023

**Prepared by**

Dell Tech Laboratories Ltd. Phone: (519) 858-5021

**Further information**

Not available.