

1. Identification

Product identifier	SONAX PROFILINE Ceramic Coating CC Vinyl + PPF	
Other means of identification	Article number: 02790000-755	
Recommended use	Not available.	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/Distributor information		
Manufacturer		
Company name	Sonax GmbH	
Address	Münchener Strasse 75 D-86633 Neuburg/Donau Germany	
Telephone	Phone:	0049 84 31 53-0
E-mail	Not available.	
Emergency phone number	Emergency Contact (24h)	GBK/Infotrac ID 91785: (USA domestic) 1 800 535 5053 or international (001) 352 323
Supplier	Vision Investments, LLC 17414 Tiller Court Westfield, IN 46074 US Email: info@sonaxusa.com Phone: 1-317-295-7056	

2. Hazard identification

Physical hazards	Flammable liquids	Category 3
Health hazards	Serious eye damage/eye irritation	Category 2A
	Reproductive toxicity	Category 1B
Environmental hazards	Not classified.	
WHMIS 2015 defined hazards	Not classified	
Label elements		



Signal word	Danger
Hazard statement	Flammable liquid and vapour. Causes serious eye irritation. May damage fertility or the unborn child.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Wash thoroughly after handling. Wear protective gloves, protective clothing, eye protection and face protection.
Response	IF exposed or concerned: Get medical attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. In case of fire: Use appropriate media to extinguish.
Storage	Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of container in accordance with local, regional, national and international regulations.
WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC)	None known

WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC)	None known
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/Information on ingredients

Mixture

Chemical name	Common name and synonyms	CAS number	%
Titanic acid, tetrabutyl ester		5593-70-4	1 - 5
Methanol		67-56-1	0.1 - 1
Toluene		108-88-3	0.1 - 1

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret. US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical attention. If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Foam. Dry chemical powder. Carbon dioxide (CO ₂). Water spray. Sand.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Flammable liquid and vapour.
Hazardous combustion products	Not available

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	---

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Avoid contact with eyes, skin and clothing. Avoid breathing mist or vapour. Do not swallow. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Pregnant or breastfeeding women must not handle this product. When using do not smoke. Observe good industrial hygiene practices. Take off contaminated clothing and wash before reuse. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Keep out of the reach of children. Keep away from heat, sparks and open flame. Keep container tightly closed in a cool, dry and well-ventilated place. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). Store away from foodstuffs. Protect contents from humidity. Recommended storage temperature: 20 °C / 68 °F Store locked up.

8. Exposure controls/Personal protection

Occupational exposure limits**Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)**

Components	Type	Value
Methanol (CAS 67-56-1)	STEL	328 mg/m3 250 ppm
	TWA	262 mg/m3 200 ppm
Toluene (CAS 108-88-3)	TWA	188 mg/m3 50 ppm

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value
Methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value
Methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

Canada. New Brunswick Regulation 91-191, as amended

Components	Type	Value
Methanol (CAS 67-56-1)	STEL	328 mg/m3 250 ppm
	TWA	262 mg/m3 200 ppm
Toluene (CAS 108-88-3)	TWA	188 mg/m3 50 ppm

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value
Methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Type	Value
Methanol (CAS 67-56-1)	STEL	328 mg/m3
		250 ppm
	TWA	262 mg/m3 200 ppm
Toluene (CAS 108-88-3)	TWA	188 mg/m3 50 ppm

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 2020. S-15.1 Reg. 10. Table 18)

Components	Type	Value
Methanol (CAS 67-56-1)	15 minute	250 ppm
	8 hour	200 ppm
Toluene (CAS 108-88-3)	15 minute	60 ppm
	8 hour	50 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Methanol (CAS 67-56-1)	PEL	260 mg/m3 200 ppm

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Methanol (CAS 67-56-1)	STEL	325 mg/m3 250 ppm
		TWA
	Toluene (CAS 108-88-3)	STEL
TWA		375 mg/m3 100 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Methanol (CAS 67-56-1)	15 mg/L	Methanol	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/L	Toluene	Urine	*
	0.02 mg/L	Toluene	Blood	*

* - For sampling details, please see the source document.

Exposure guidelines

Canada - Alberta OELs: Skin designation

Methanol (CAS 67-56-1)

Can be absorbed through the skin.

Toluene (CAS 108-88-3)	Can be absorbed through the skin.
Canada - British Columbia OELs: Skin designation	
Methanol (CAS 67-56-1)	Can be absorbed through the skin.
Canada - Manitoba OELs: Skin designation	
Methanol (CAS 67-56-1)	Danger of cutaneous absorption
Canada - Ontario OELs: Skin designation	
Methanol (CAS 67-56-1)	Can be absorbed through the skin.
Canada - Quebec OELs: Skin designation	
Methanol (CAS 67-56-1)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.
Canada - Saskatchewan OELs: Skin designation	
Methanol (CAS 67-56-1)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.
US ACGIH Threshold Limit Values: Skin designation	
Methanol (CAS 67-56-1)	Danger of cutaneous absorption
US NIOSH Pocket Guide to Chemical Hazards: Skin designation	
Methanol (CAS 67-56-1)	Can be absorbed through the skin.
Appropriate engineering controls	Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear safety glasses with side shields.
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves.
Other	Wear suitable protective clothing. Use of an impervious apron is recommended.
Respiratory protection	Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).
Thermal hazards	Not available.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Liquid
Physical state	Liquid.
Form	Liquid.
Colour	Colourless
Odour	Solvent-like
Odour threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	143 °C (289.4 °F)
Specific gravity	Not available.
Flash point	28.0 °C (82.4 °F)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.

Vapour pressure	Not available.
Vapour density	Not available.
Relative density	Not available.
Solubility(ies)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Pour point	Not available.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Chemical stability	Material is stable under normal conditions.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point.
Incompatible materials	Strong oxidising agents.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon.

11. Toxicological information

Routes of exposure	Inhalation. Eye contact.
Information on likely routes of exposure	
Ingestion	May cause stomach distress, nausea or vomiting.
Inhalation	Prolonged inhalation may be harmful.
Skin contact	Prolonged or repeated contact may dry skin and cause irritation.
Eye contact	Causes serious eye irritation.
Symptoms related to the physical, chemical and toxicological characteristics	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity Not known.

Components	Species	Test Results
Methanol (CAS 67-56-1)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	17100 mg/kg, ECHA
<i>Inhalation</i>		
LC50	Cat	43.7 mg/L, 6 Hours, ECHA
<i>Oral</i>		
LD50	Rat	> 2528 mg/kg, ECHA
Titanic acid, tetrabutyl ester (CAS 5593-70-4)		
Acute		
<i>Dermal</i>		
LD50	Not available	
<i>Inhalation</i>		
LC50	Not available	
<i>Oral</i>		
LD50	Rat	> 2000 mg/kg, ECHA

Components	Species	Test Results
Toluene (CAS 108-88-3)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	25.7 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	5580 mg/kg, ECHA
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Exposure minutes	Not available.	
Erythema value	Not available.	
Oedema value	Not available.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Corneal opacity value	Not available.	
Iris lesion value	Not available.	
Conjunctival reddening value	Not available.	
Conjunctival oedema value	Not available.	
Recover days	Not available.	
Respiratory or skin sensitisation		
Respiratory sensitisation	Not a respiratory sensitizer.	
Skin sensitisation	This product is not expected to cause skin sensitisation.	
Mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Not classifiable as to carcinogenicity to humans.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Toluene (CAS 108-88-3)	Volume 47, Volume 71 - 3 Not classifiable as to carcinogenicity to humans.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)		
Not listed.		
Reproductive toxicity	May damage fertility or the unborn child.	
Teratogenicity	Not available.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Prolonged inhalation may be harmful.	

12. Ecological information

Ecotoxicity	See below		
Ecotoxicological data			
Components	Species	Test Results	
Methanol (CAS 67-56-1)			
Aquatic			
Crustacea	EC50	Water flea (<i>Daphnia magna</i>)	> 10000 mg/L, 48 hours
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>)	> 100 mg/L, 96 hours
Toluene (CAS 108-88-3)			
Algae	IC50	Algae	433 mg/L, 72 Hours
Crustacea	EC50	Daphnia	7.645 mg/L, 48 Hours
Aquatic			
Crustacea	EC50	Water flea (<i>Daphnia magna</i>)	5.46 - 9.83 mg/L, 48 hours

Components	Species	Test Results
Fish	LC50 Coho salmon, silver salmon (Oncorhynchus kisutch)	8.11 mg/L, 96 hours
Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.	
Bioaccumulative potential		
Mobility in soil	No data available.	
Mobility in general	Not available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

Transport of Dangerous Goods (TDG) Proof of Classification Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.

U.S. Department of Transportation (DOT)

Basic shipping requirements:

UN number	UN1993
Proper shipping name	Flammable liquids, n.o.s.
Technical name	Methyl triethoxysilane
Technical name	Siloxanes And Silicones, Me Methoxy Polymers With Me Silsesquinoxanes
Hazard class	3
Packing group	III

Transportation of Dangerous Goods (TDG - Canada)

Basic shipping requirements:

UN number	UN1993
Proper shipping name	FLAMMABLE LIQUID, N.O.S.
Technical name	Methyl triethoxysilane
Technical name	Siloxanes And Silicones, Me Methoxy Polymers With Me Silsesquinoxanes
Hazard class	3
Packing group	III

DOT





15. Regulatory information

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Methanol (CAS 67-56-1)	1 TONNES
Toluene (CAS 108-88-3)	1 TONNES

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Toluene (CAS 108-88-3)	Class B
------------------------	---------

WHMIS 2015 Exemptions Not applicable

US Federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Methanol (CAS 67-56-1)	Listed.
Toluene (CAS 108-88-3)	Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance No

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Flammable (gases, aerosols, liquids, or solids)
Serious eye damage or eye irritation
Reproductive toxicity

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Methanol (CAS 67-56-1)
Toluene (CAS 108-88-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

US state regulations

US - California Hazardous Substances (Director's): Listed substance

Methanol (CAS 67-56-1)	Listed.
Toluene (CAS 108-88-3)	Listed.

US - Illinois Chemical Safety Act: Listed substance

Methanol (CAS 67-56-1)
Toluene (CAS 108-88-3)

US - Louisiana Spill Reporting: Listed substance

Methanol (CAS 67-56-1)	Listed.
Toluene (CAS 108-88-3)	Listed.

US - Michigan Critical Materials Register: Parameter number

Toluene (CAS 108-88-3)

US - Minnesota Haz Subs: Listed substance

Methanol (CAS 67-56-1) Listed.

Toluene (CAS 108-88-3) Listed.

US - North Carolina Toxic Air Pollutants: Listed substance

Toluene (CAS 108-88-3)

US - Texas Effects Screening Levels: Listed substance

Methanol (CAS 67-56-1) Listed.

Titanic acid, tetrabutyl ester (CAS 5593-70-4) Listed.

Toluene (CAS 108-88-3) Listed.

US - Washington Chemical of High Concern to Children: Listed substance

Toluene (CAS 108-88-3)

US. Massachusetts RTK - Substance List

Methanol (CAS 67-56-1)

Toluene (CAS 108-88-3)

US. New Jersey Worker and Community Right-to-Know Act

Methanol (CAS 67-56-1)

Toluene (CAS 108-88-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Methanol (CAS 67-56-1)

Toluene (CAS 108-88-3)

US. Rhode Island RTK

Methanol (CAS 67-56-1)

Toluene (CAS 108-88-3)

US. California Proposition 65

WARNING: This product can expose you to chemicals including Toluene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Developmental toxin

Methanol (CAS 67-56-1) Listed: March 16, 2012

Toluene (CAS 108-88-3) Listed: January 1, 1991

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	/ 1
FLAMMABILITY	3
PHYSICAL HAZARD	0
PERSONAL PROTECTION	

**Disclaimer**

The information in the safety data sheet was written by Dell Tech Laboratories Ltd. (www.delltech.com) based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date	06-November-2023
Version No.	01
Effective date	06-November-2023
Prepared by	Dell Tech Laboratories Ltd. Phone: (519) 858-5021
Further information	Not available.